



QDD03

Electric Tractor 0.3t

EP EQUIPMENT CO.,LTD
www.ep-ep.com

Electric Tractor 0.3t QDD03

distinguishing mark				
1.1	Manufacturer			EP
1.2	Model designation			Tricycle
1.3	Drive unit			Electric
1.4	rated capacity	Q	kg	250
1.5	Wheelbase	y	mm	1205
Weight				
2.1	Service weight (include battery)		kg	125
2.2	Axle loading, laden driving side/loading side		kg	305/70
2.3	Axle loading, unladen driving side/loading side		kg	85/40
Types,Chassis				
3.1	Tyre type Driving w heels/Loading w heels			
3.2	Tyre size, driving w heels (diameter×width)		mm	Φ250×85
3.3	Tyre size, loading w heels (diameter×width)		mm	Φ280×65
3.4	Wheels, number driving, caster/loading (x=drive w heels)		mm	2x +1
Dimensions				
4.1	Height draw bar in driving position min./max.	h_{14}	mm	950/1050
4.2	Overall length	l_1	mm	1550
4.3	Length to face of forks	h_{13}	mm	300
4.4	Overall width	b_1	mm	810
4.5	Fork dimensions	s/ e/ l	mm	600×800
4.6	Ground clearance, center of wheelbase	m_2	mm	60
4.7	Turning radius	Wa	mm	1550
Performance data				
5.1	Travel speed, laden/ unladen		km/ h	12 14
5.2	Max. gradeability, laden/unladen		%	8/16
5.30	Service brake type			Electromagnetic
Electric-engine				
6.1	Drive motor rating S2 60 min		kW	0.8
6.2	The maximum allowed size battery		mm	130x165x150
6.3	Battery voltage/nominal capacity K5		V/ Ah	24/30
6.4	Battery weight		kg	
Addition data				
8.1	Type of drive unit			DC
10.1	Steering type			Machanical Steering
10.2	Sound pressure level at the driver's ear		dB (A)	74

1.The parameters in the table are of the standard model. For more
2.The parameters are subject to change without notice.

