



QDD25P

Electric Tractor 2.5t

EP EQUIPMENT CO.,LTD
www.ep-ep.com

Electric tractor 2.5t QDD25P

Distinguishing mark				
1.1	Manufacturer		EP	
1.2	Model designation		QDD25P	
1.3	Drive unit		Electrical	
1.4	Operator type		Standing	
1.5	rated capacity	Q	kg	450
	Rated drawbar pull		kg	2000
1.9	Wheelbase	y	mm	1055
Weight				
2.1	Service weight (include battery)		kg	750
2.2	Axle loading, laden Driving/loading		kg	640/560
2.3	Axle loading, unladen Driving/loading		kg	450/300
Types,Chassis				
3.1	Tyre type driving wheels/Loading wheels			solid rubber
3.2	Tyre size, driving wheels (diameter*width)		mm	4.00-8
3.3	Tyre size, steering wheels (diameter*width)		mm	15x4.5
3.5	Wheels, number driving/loading (x=drive wheels)		mm	1/2x
3.7	Track width,rear,loading side	b ₁₁	mm	664
Dimensions				
4.7	Height of overhead , No ladder	h ₈	mm	1265
	Height of overhead , Ladder with 3 stairs		mm	1940
	Height of overhead , Ladder with 5 stairs		mm	2480
4.12	Tow coupling height	h ₁₀	mm	320
4.13	Loading height, unladen	h ₁₁	mm	590
4.16	Length of loading surface	l ₃	mm	1300
4.18	Width of loading surface	b ₉	mm	740
4.19	Overall length , No ladder	l ₁	mm	2190
	Overall length , Ladder with 3 stairs		mm	2300
	Overall length , Ladder with 5 stairs		mm	2400
4.21	Overall width	b ₇ / b ₂	mm	780
4.32	Ground clearance, center of wheelbase	m ₂	mm	74
4.35	turning radius	Wa	mm	1385
Performance data				
5.1	Travel speed, laden/ unladen		km/ h	7/7
5.5	Drawbar pull, laden/unladen		N	640
5.6	Max. drawbar pull, laden/unladen		N	2500
5.8	Max. gradeability, laden/unladen		%	5/20
5.10.1	Service brake type			hydraulic+Mechanical
5.10.2	Park brake type			hydraulic+Mechanical
Electric-engine				
6.1	Drive motor rating S2 60 min		kW	3
6.3	The maximum allowed size battery		mm	/
6.4	Battery voltage/nominal capacity K5			48/200
6.5	Battery weight		kg	200
Addition data				
8.4	Sound pressure level at the driver's ear		dB (A)	70
8.5	Traction pin type		dB (A)	Bolt type

1.The parameters in the table are of the standard model. For more information, please contact us.

2.The parameters are subject to change without notice.

